



# EXCELAM-

**Q1400COLD/RS**  
**Q1400COLD/RSER**  
**Q1600COLD/RS**  
**Q1600COLD/RSER**  
**Q1600COMBI/RSER**

Prographics Roll Laminator  
High speed Laminating (Up to 5m/min)



- High speed Laminating (Up to 5m/min)
- Strengthen Main Motor for better drive torque and its durability
- Rewinder connected to the powerful main motor
- Top retractor for releasing liner
- Easy to use for outer retractor tension control
- Designed for dual film core and stronger unwinder shaft
- Sub heating system (upper roller)  
: 1600COMBI/RSER
- Mounting up to 13mm
- Back Trimmer for limited web removal



**EXCELAM-QCOLD Series**

[www.gmp.com](http://www.gmp.com)



This cover is laminated with GMP NYLONEX by using GMP PIONEER II-8000BC. NYLONEX is curling and scratch-free, high glossy super-bond-film.

**GMP GMP CO., LTD.**



# EXCELAM-

Q1400COLD/RS  
Q1600COLD/RS  
Q1600COMBI/RSER

Q1400COLD/RSER  
Q1600COLD/RSER

## Roll Laminator

**EXCELAM-Q COLD** is the perfect machine for wide range of service in a copy shop environment or as a print finishing. Ideal for laminating posters, ink-jet prints, leaflets and maps with superb results and for truly professional mounting up to 13mm GMP LAMIFOAM (Foamboard).

Super Cold Laminating results on wide ranges of Cold films from 25micron & 50micron GMP Crystalex Film (Polyester Base Cold Film) Including 75micron & 100 micron GMP Pronex Cold UV Film (Soft Touch Cold Film). Features include variable speed and pressure adjust handle, for laminating thickness and pressure, mounting thickness setting.



## Specifications

Model Name	EXCELAM-Q1400COLD/RS	EXCELAM-Q1600COLD/RS	EXCELAM-Q1600COMBI/RSER
MAX. Laminating Speed	5m/min	5m/min	5m/min
Laminating Width	1400mm	1600mm	1600mm
Laminating Films	75mic~500mic	75mic~500mic	25mic~500mic
Thickness of substrate(Paper)	80g/ m <sup>2</sup> ~ 350g/ m <sup>2</sup>	80g/ m <sup>2</sup> ~ 350g/ m <sup>2</sup>	80g/ m <sup>2</sup> ~ 350g/ m <sup>2</sup>
MAX. Thickness Mount	13mm	13mm	13mm
Power Requirements	220~240V, 50/60Hz	220~240V, 50/60Hz	220~240V, 50/60Hz
Power Consumption	100W, 0.4A	100W, 0.4A	2000W, 8.3A
Warm up Time	-	-	5 minutes
Heating System	-	-	Infrared Heater
Operating Temperature	-	-	150 °C Max.
Speed Control	Knob & Volume	Knob & Volume	Key Pad
Temperature Control	-	-	Key Pad
Pressure Adjustment	Manual (6step)	Manual (6step)	Manual (6step)
Film Core	BD Core	BD Core	BD Core
Dimensions(WxLxH)	1640 x 750 x 1200mm	1840x 750 x 1200mm	1840x 750 x 1200mm
Type of Main Motor	DC W-Geard Motor /36V80	DC W-Geard Motor /36V80	DC W-Geard Motor /36V80
Type of Rewinder Motor	Link to Main Motor	Link to Main Motor	Link to Main Motor

GMP reserves the right to after change specifications without prior notice.

